... for a cleaner world :-

HOT WATER +HIGH-PRESSURE An Unbeatable Advantage



OERTZEN Manufactures of HOT WATER High-Pressure Jetting Units

Designed to remove stubborn/ heavy dirt layers, the combination of high temperatures and high-pressure water make for an effcient and reliable cleaning unit.

The OERTZEN hot water range is available from 120 bar up to 210 bar.



Hot water high-pressure units are designed for use in:

- Construction companies
- Forwarders
- Industrial cleaning contractors
- Truck repair workshops
- Municipalities
- Transport fleets
- Food industry
- Cleaning contractors
- Agriculture



ROYALFLUSH



Technical Data Flow Unloading pressure Working pressure/adjustable max. Water temperature Hydrodyn. capacity (I/min x bar) **Total power connected** Drive **Pump speed** Start/stop Autom. anti-scalant Fuel tank **Detergent tank** Dimensions (L x W x H mm)

Weight

Order No.

Compact 120 K 540 l/h 140 bar 120 bar 30 - 90°C 1.080 2,4 kW 230V/1~50 Hz 2.800 1/min Injection 720x500x600 75 kg 10.000.120

JuniorPower 800 l/h 180 bar 160 bar 30 - 140°C 2.130 5,5 kW 400V/3~50 Hz 2.800 1/min standard standard 121 81 950x670x810 88 kg 10.000.012

EuroPower 2 900 l/h 195 bar 180 bar 30 - 140°C 2.700 6,5 kW 400V/3~50 Hz 1.420 1/min standard standard 201 201 1.050x700x880 142 kg 10.000.013

SuperMagnum 220 ELC | SuperMagnum 270 ELC 960 l/h 230 bar 210 bar 30 - 140°C 3.360 6,9 kW 400V/3~50 Hz 1.420 1/min standard standard 201 15 I 1.020x860x650 145 kg 10.000.025

1.320 l/h 230 bar 210 bar 30 - 140°C 4.620 8,8 kW 400V/3~50 Hz 1.420 1/min standard standard 30 I 161 1.310x770x95 210 kg 10.000.270

Standard Equipment: 10 m high-pressure hose (300 respectively 500 bar), highpressure safety pistol and double lance (except Compact 120 K, Junior Power)

Reliable machines due to durable components

Hot water high-pressure cleaners manufactured by OERTZEN are reliable and efficient machines which easily solve the most difficult of daily cleaning tasks.

Fitted with smooth running, durable inline plunger pumps, which have an excellent flowrate at a low pump speed. The clear operating panel allows for easy and safe handling of the machine, which is one more advantage for quick work and cleanliness.



External located filling ports for refilling the integrated tanks, make these high-pressure cleaners easy and troublefree to work with. OERTZEN Turbo Blasters are special nozzles with rotary point jet in order to achieve high impact pressure. Excellent removal and flushing efficiency.



e.g. Turbo Blaster 065 for OERTZEN SuperMagnum 270 ELC



Stainless steel boilers safely and economically heat up the water. The benefits of vertical burners guarantee an environmental burning process.



Particular models can be equipped with integrated hose reels, giving opportunity to clean "hard to reach" areas.



All OERTZEN machines conform to relevant European Safety Regulations.
A Declaration of Conformity is provided with each unit.



The OERTZEN floor cleaners have an impressing cleaning capacity.

An integral skirt ensures that the water spray is encapsulated – avoiding over spray of the area.



The OERTZEN hot water units are also available as stationary machines. Please request our Stationary Unit brochure.

The standard flat stream nozzle easily removes most dirt layers within shortest possible time. For difficult cleaning applications we have a comprehensive accessory range, offering special nozzles.



OERTZEN appointed dealer:

