

TW 1250

- Efficient and time-saving: Fast drying and high cleaning performance
- Clean emptying: Practical drain connection for dirty water, without tilting
- Continuously adjustable pump pressure (2–11 bar) – allows individual adjustment depending on the degree of soiling, for even finer control and deeper cleaning

TW 1250



Stepless pressure regulation



Easy access to the tank



Stair climbing thanks to big castors



Carpet adapter holder

Technical data

Total power	1700 W / 230 V
Vacuum	250 mbar
Fresh water capacity	35 l
Dirty water capacity	40 l
Pump pressure max.	2-11 bar adjustable
Spray pressure	up to 3,6 l/min
Airflow capacity	60 l/sec
Vacuum width	30 cm
Cable length	20 m
Weight	44 kg
Measurements l / w / h	82 / 41 / 84 cm
Item number	125.000VDE

Scope of delivery

125.400	Spray and suction hose, high pressure, 4 m
611.000	Carpet adapter, 4 jet 30 cm, alu high pressure

Special accessories

681.000	Filling up hose for fresh water, 2 m
660.000	Pre-spray lance with 10 m hose

Special accessories tools/ adapter



617.000
Upholstery tool 8 cm, PVC, anthracite, with nozzle inside



618.000
Upholstery tool 9 cm, alu, with nozzle outside



622.000
Wall and ceiling tool, 9 cm



638.000
Hard floor adapter, 37 cm, Ø 38 mm

Cleanfix / 2025-04

Cleanfix Reinigungssysteme AG, Stettenstrasse 15, 9247 Henau
+41 58 329 45 45, info@cleanfix.com, www.cleanfix.com